

Flashlight Police Torch



User Manual

iiglo

Features

- Compact LEP flashlight with a service life of up to 10,000 hours
- USB-C Charging port provides a 3 times faster charging speed
- Powered by a single 21700 5100mAh rechargeable battery, or a single 18650 3100mAh rechargeable battery
- Tactical tail switch for convenient operation
- Special designed stainless steel aggressive bezel
- CNC Machined aircraft grade aluminium body
- Type III Hard anodized finish
- Highly focused beam for maximum distance.
- Streamlined body design with tactical knurling for firm grip
- Highly efficient circuit design provides maximum runtimes
- Intelligent temperature controlled light output for user safety
- Special design for border, public security, prisons, electricity, airports, terminals, troops, factories and mines, and a variety of field lighting and signal use

Accessories

1 x iiglo 21700 5100mAh Rechargeable Battery; 1 x USB-C Cable;
1 x Removable Clip; 1 x 18650 Battery Adaptor; 1 x Red Filter; 1 x Green Filter;
2 x O-rings; 1 x User Manual; 1 x Warranty Card; 1 x Battery Warning Card

Specifications

Size: 149.5mm(length) x 31.5mm(head diameter) x 25.4mm(tube diameter)
Weight: 128g without battery

Technical Parameter

FL1 STANDARD	1x 21700 battery
	450 lumens
	3h 30min
	1217m (Beam Distance)
	370,000cd
	Full-width 3.1° (10%)



Notice: The above-mentioned parameters (tested with 1 x iiglo 21700 5100mAh battery) are approximate and may vary from flashlights, batteries, and environment.

Battery Specifications

Type	Dimensions	Nominal Voltage	Usability	
iiglo-510A	21700	3.7V	Recommended	✓
iiglo-310A	18650	3.7V	Recommended	✓
Non-rechargeable Battery	CR123A	3V	Banned	X

Notice: CR123 battery and 16340 battery are banned.
Quality 21700 or 18650 batteries with circuit protection will reduce the potential risk.
iiglo-510A 21700 battery or iiglo-310A 18650 battery is strongly recommended.

Operation Instruction

Tail switch: Tap for momentary on, click for Constant on.
Twist the protective USB Ring-cover sleeve to recharge the flashlight.

LED Charging Indicator

Red means under charging
Green means charging completed.

Low-Voltage Warning

W10 GENII will turn it off directly when the brightness dim to 30% of the normal brightness.

Warning

1. iiglo Flashlight is a high intensity lighting device and is capable of causing eye damage. Avoid shining the light directly into the eyes to humans or animals.
2. Applications must be treated with caution and handled with care.
3. Quality batteries with circuit protection will reduce the potential risk.
4. When the iiglo Flashlight is stored in a backpack or unused for extended period, it is suggested to loosen the tube to cut off the power entirely to prevent the accidental activation of the flashlight.
5. W10 is purchased by only for professional users of the military and police (It is not a civilian industry product).

Usage and Maintenance

- Do not disassemble the sealed head as doing so may cause damage to the flashlight and will void the warranty.
 - High-power flashlights need batteries capable of high current output. We strongly recommend using Acebeam approved batteries for best performance and safety.
 - Remove the battery from the flashlight if you will not be using the light for an extended period.
 - Replace the O-rings if they become stretched or damaged. Regularly lubricate the O-rings.
 - Clean the contacts of your light periodically.
- There may be several reasons for a flickering or malfunctioning light.
- Reason 1:** The batteries need to be recharged or replaced.
Solution : Recharge or replace batteries.
- Reason 2:** The PCB board contact or battery contacts are dirty.
Solution : Clean the contact points with an alcohol soaked cotton swab.
- If the above methods do not solve the issue, please contact your distributor and refer to the warranty policy.

Imported by iiglo | Østre Kullerød 4, N-3241 Sandefjord, Norway
www.iiglo.com | Made in China

